

PAVER & CONCRETE SOLVENT

DESCRIPTION

Colormaker Paver & Concrete Solvent is used as thinner for following products

- **Acrylmeric Concrete Sealer**
- **Acrylmeric Petrol & Oil Concrete Sealer**
- **Acrylmeric Slate Sealer**

Usage:

Thin only first coat when applying on bare surface.

First coat may be thinned up to 10% with 'Paver and Concrete Solvent' so as to maximise penetration and minimise bubbling.

Paver & Concrete Solvent can also be used for cleaning equipment.

PACKAGING

Available in 20L, 4L and 1L metal screw-top containers. Reseal the container immediately after use.

HEALTH & SAFETY

This product is flammable. Keep away from naked flame. In the event of fire, extinguish with foam or CO₂. Avoid breathing the vapour and wear appropriate vapour mask during use. Provide adequate ventilation whilst using in enclosed areas. Avoid contact with the skin and wear protective eyewear. If swallowed, **DO NOT** induce vomiting, give a glass of water and seek immediate medical attention. If contact with the skin, wash off with soap and clean water. If irritation occurs seek immediate medical advice. SDS available upon request.

VER1805

Product Disclaimer:

The technical information and/or application advice given in this publication represents the present state of our knowledge, and is believed to be reliable. Buyers and intended users of Colormaker Industries products should read the TDS carefully and then conduct their own assessment to confirm the suitability of the product, including in conjunction with other products, and the types of surfaces to, and the manner in which, the product will be applied. Colormaker Industries offers no warranty of performance based on the above information either expressed or implied